

How To Fit Your 2 Point Harness

Step 1

Undo one of the front clips and the 2 clips for the back. Place your harness on your dog's back as shown below. The D ring should be towards your dogs tail. **(Figure 1)**



Step 2

The front part of the harness is attached to an O ring. Fit the front piece around the base of your dog's neck and connect the clips. Adjust the sliders if required. **(Figure 2)**



Step 3

Place the underneath part of the harness between your dog's front legs. Adjust the sliders if required and fasten the clips either side of your dog's chest **(Figure 3)**



Step 4

Adjust the sliders to ensure the harness fits correctly.

You should be able to get 2 fingers in between the neck and chest.

(See Figures 4 and 5)

(Figure 4)



(Figure 5)



Step 6

To ensure the harness is in the correct position on the chest adjust the webbing between your dog's front legs
(Figure 6)



Step 7

You should be able to place 2 fingers between the chest strap and your dogs elbow when they are standing
(Figure 7)



Step 8

Attach your training lead. The clip that is closest to the label should be on the D ring at the back of the harness
(Figure 8)



Check your harness regularly to ensure that it fits your dog or puppy correctly. Adjust the 5 sliders as necessary.

1. Coat thickness: if your dog has been groomed recently or if they are between grooms, check your harness fits correctly. Ensuring you can only get 2 fingers in between the straps.
2. Has your puppy grown?
3. Has your dog gained or lost weight?
4. Are you using the harness over a coat?

We can make adjustments and repairs to your harness.

Please wash your harness before returning to us for repairs or alterations. Harnesses and leads can be washed at 40°C.

We take every care to ensure the quality and durability of our products and will advise on the correct use. We offer to refund you if you are not satisfied with our product but cannot accept responsibility for any loss or damage caused using our products.